Fiocchetti
THE COLD MANUFACTURER

Product technical data sheet

MORTUARY REFRIGERATOR 2 BODIES

Cod. MOR0002



Disclaimer:
Images are purely indicative. The features and the accessories of the products may differ according to model and application.

General features

Temperature range	-5°C / +5°C *available also with negative temperature -10 / -20 °C*
Capacity	2 bodies on 2 levels
External Dimensions (WxDxH)	cm 89x238,7x191,3 (TN and BT version) *External dimensions without monoblock unit: cm 89x238,7x146,8* *Weight: 325 Kg*
Structure and Insulation	stainless steel 18/10 AISI 304 inside and outside; insulation polyurethane thickness 70 mm
Door	n.2 doors)
Key Lock	
Rollers	Castors with brakes
Light	
Internal equipment	n. 2 steel body trays
Controller	Digital electronic thermostat
Alarms	Acoustic and Visual far temperature deviations and failures
Refrigeration Type	Ventilated
Defrost	Automatic with automatic evaporation of the condensate water

Technical data

Details	• *Refrigerant type: R290, CFC free* • *Mains Voltage 220V/1/50Hz* • *HP 3/4 E ;kW 0,5 (-20°C model: HP 1,7 E; kW 1,35)* • *Refrigerating capacity: 1335 W (-20°C model: 1184 W)* • *Ambient Temperature: + 10/+32 °C; Humidity 60%*
In accordance with	2006/42/CE, 2014/30/CE, 2014/35/CE and following modifications
Package	Strong cardbox on wooden pallet *Dim. cm.102x248x210; Kg.365* *Wooden crate on wooden pallet available: dim. cm.112x254x216; Kg.480*
note	Also available with negative temperature (-10 / -20 °C)

FIOCCHETTI SCIENTIFIC S.R.L.
Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352
Phone +39 0522 976232 - Fax +39 0522 976028
www.fiocchetti.com - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it

Accessories

DMLP UNIT	External module with DMLP DIGITAL MONITOR: Monitor/alarm/recording system with rechargeable battery - Temperatures and alarms recorder on removable Secure Digital (SD Back-Up memory): it can store 5 years data, recording temperature and alarms every minute. The SD card can be connected to any PC: a software (capture) is included, so that you can download, save and print all data from your PC - Battery backup: ensures alarms and recording of temperatures even in case of power failure. The battery system lasts about 12 hours. - Dry contact for remote connection + RS485 port
DMLP PRINTER	
Additional body tray	
Hydraulic trolley cm 32 - 165	
Hydraulic trolley with 12V electrical adjustment cm 32 - 165	
60 Hz Frequency	

FIOCCHETTI SCIENTIFIC S.R.L.
Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352
Phone +39 0522 976232 - Fax +39 0522 976028
www.fiocchetti.com - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it