Fiocchetti
THE COLD MANUFACTURER

Product technical data sheet

MORTUARY CHAMBER 2 BODIES SIDE LOADING

Cod. MCL0002



Disclaimer:
Images are purely indicative. The features and the accessories of the products may differ according to model and application.

Characteristics

Temperature range	+2 /+8 °C or -15 /-20 °C
Capacity	2 bodies on 2 levels
External Dimensions (WxDxH)	cm 240x105x253 *External dimensions without monoblock unit: cm 240 x 105 x 208*
Structure and Insulation	White coated steel inside and outside; insulation polyurethane thickness 80 mm
Door	n.2 doors with side opening
Key Lock	
Light	
Internal equipment	n.2 steel body trays
Controller	Digital electronic thermostat
Alarms	Acoustic and Visual for temperature deviations and failures
Refrigeration Type	Ventilated
Defrost	Automatic with automatic evaporation of the condensate water

Technical data

Details	· Refrigerant type: R290, CFC free · Mains Voltage 220V/1/50Hz · Ambient Temperature: +10/+32 °C; Humidity 60% · Connector: Schuko
In accordance with	2006/42/CE, 2014/30/CE, 2014/35/CE and following modifications
Package	Chamber to be installed on site, packed in cellophane on pallet, monoblock in strong cardboard on wooden pallet

FIOCCHETTI SCIENTIFIC S.R.L.
Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352
Phone +39 0522 976232 - Fax +39 0522 976028
www.fiocchetti.com - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it

Accessories

Internal covering in stainless steel	
External covering in stainless steel	
DMLP UNIT	• External module with DMLP DIGITAL MONITOR: Monitor/alarm/recording system with rechargeable battery • Temperatures and alarms recorder on removable Secure Digital (SD Back-Up memory): it can store 5 years data, recording temperature and alarms every minute. • The SD card can be connected to any PC: a software (Capture) is included, so that you can download, save and print all data from your PC • Battery backup: ensures alarms and recording of temperatures even in case of power failure. The battery system lasts about 12 hours. • Dry contact for remote connection + RS485 port
DMLP PRINTER	
Voltage 220V/1/60Hz	
Additional body tray	
Hydraulic trolley with electrical adjustment H cm 39 - 202	
Wooden crate Package	

FIOCCHETTI SCIENTIFIC S.R.L.
Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352
Phone +39 0522 976232 - Fax +39 0522 976028
www.fiocchetti.com - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it